

Lecture: Introduction to Convex Optimization

Zaiwen Wen

*Beijing International Center For Mathematical Research
Peking University*

<http://bicmr.pku.edu.cn/~wenzw/opt-2014-fall.html>
wenzw@pku.edu.cn

Acknowledgement: this slides is based on Prof. Lieven Vandenberghe's lecture notes

Introduction

- mathematical optimization
- least-squares and linear programming
- convex optimization
- example
- course goals and topics
- nonlinear optimization
- brief history of convex optimization

Mathematical optimization

(mathematical) optimization problem

$$\begin{array}{ll} \min & f_0(x) \\ \text{s.t.} & f_i(x) \leq b_i, \quad i = 1, \dots, m \end{array}$$

- $x = (x_1, x_2, \dots, x_n)$: optimization variables
- $f_0 : \mathbb{R}^n \rightarrow \mathbb{R}$: objective function
- $f_i : \mathbb{R}^n \rightarrow \mathbb{R}, i = 1, \dots, m$: constraint functions

optimal solution x^* has smallest value of f_0 among all vectors that satisfy the constraints

Examples

portfolio optimization

- variables: amounts invested in different assets
- constraints: budget, max./min. investment per asset, minimum return
- objective: overall risk or return variance

device sizing in electronic circuits

- variables: device widths and lengths
- constraints: manufacturing limits, timing requirements, maximum area
- objective: power consumption

data fitting

- variables: model parameters
- constraints: prior information, parameter limits
- objective: measure of misfit or prediction error

Solving optimization problems

general optimization problem

- very difficult to solve
- methods involve some compromise, *e.g.*, very long computation time, or not always finding the solution

exceptions : certain problem classes can be solved efficiently and reliably

- least-squares problems
- linear programming problems
- convex optimization problems

Least-squares

$$\min \|Ax - b\|_2^2$$

solving least-squares problems

- analytical solution: $x^* = (A^T A)^{-1} A^T b$
- reliable and efficient algorithms and software
- computation time proportional to $n^2 k$ ($A \in \mathbb{R}^{k \times n}$); less if structured
- a mature technology

using least-squares

- least-squares problems are easy to recognize
- a few standard techniques increase flexibility (*e.g.*, including weights, adding regularization terms)

Linear programming

$$\begin{array}{ll} \min & c^T x \\ \text{s.t.} & a_i^T x \leq b_i, \quad i = 1, \dots, m \end{array}$$

solving linear programs

- no analytical formula for solution
- reliable and efficient algorithms and software
- computation time proportional to n^2m if $m \geq n$; less with structure
- a mature technology

using linear programming

- not as easy to recognize as least-squares problems
- a few standard tricks used to convert problems into linear programs (*e.g.*, problems involving ℓ_1 - or ℓ_∞ - norms, piecewise-linear functions)

Convex optimization problem

$$\begin{aligned} \min \quad & f_0(x) \\ \text{s.t.} \quad & f_i(x) \leq b_i, \quad i = 1, \dots, m \end{aligned}$$

- objective and constraint functions are convex:

$$f_i(\alpha x + \beta y) \leq \alpha f_i(x) + \beta f_i(y)$$

if $\alpha + \beta = 1, \alpha \geq 0, \beta \geq 0$

- includes least-squares problems and linear programs as special cases

solving convex optimization problems


- no analytical solution
- reliable and efficient algorithms
- computation time (roughly) proportional to $\max\{n^3, n^2m, F\}$, where F is cost of evaluating f_i 's and their first and second derivatives
- almost a technology

using convex optimization

- often difficult to recognize
- many tricks for transforming problems into convex form
- surprisingly many problems can be solved via convex optimization

Example

m lamps illuminating n (small, flat) patches



intensity I_k at patch k depends linearly on lamp powers p_j :

$$I_k = \sum_{j=1}^m a_{kj} p_j, \quad a_{kj} = r_{kj}^{-2} \max\{\cos \theta_{kj}, 0\}$$

problem: achieve desired illumination I_{des} with bounded lamp powers

$$\min \max_{k=1, \dots, n} |\log I_k - \log I_{\text{des}}|$$

$$\text{s.t. } 0 \leq p_j \leq p_{\text{max}}, \quad j = 1, \dots, m$$

how to solve?

- 1 use uniform power: $p_j = p$, vary p
- 2 use least-squares:

$$\min \sum_{k=1}^n (I_k - I_{\text{des}})^2$$

round p_j if $p_j > p_{\text{max}}$ or $p_j < 0$

- 3 use weighted least-squares:

$$\min \sum_{k=1}^n (I_k - I_{\text{des}})^2 + \sum_{j=1}^m w_j (p_j - p_{\text{max}}/2)^2$$

iteratively adjust weights w_j until $0 \leq p_j \leq p_{\text{max}}$

- 4 use linear programming:

$$\begin{aligned} \min \quad & \max_{k=1, \dots, n} |I_k - I_{\text{des}}| \\ \text{s.t.} \quad & 0 \leq p_j \leq p_{\text{max}}, \quad j = 1, \dots, m \end{aligned}$$


which can be solved via linear programming

of course these are approximate (suboptimal) 'solutions'

- 5 use convex optimization: problem is equivalent to

$$\begin{aligned} \min \quad & f_0(p) = \max_{k=1,\dots,n} h(I_k/I_{\text{des}}) \\ \text{s.t.} \quad & 0 \leq p_j \leq p_{\text{max}}, \quad j = 1, \dots, m \end{aligned}$$

with $h(u) = \max\{u, 1/u\}$



f_0 is convex because maximum of convex functions is convex

exact solution obtained with effort \approx modest factor \times least-squares effort

additional constraints: does adding (1) or (2) below complicate the problem?

- 1 no more than half of total power is in any 10 lamps
 - 2 no more than half of the lamps are on ($p_j > 0$)
-
- answer: with (1), still easy to solve; with (2), extremely difficult
 - moral: (untrained) intuition doesn't always work; without the proper background very easy problems can appear quite similar to very difficult problems

Course goals and topics

goals

- 1 recognize/formulate problems (such as the illumination problem) as convex optimization problems
- 2 develop code for problems of moderate size (1000 lamps, 5000 patches)
- 3 characterize optimal solution (optimal power distribution), give limits of performance, etc.

topics

- 1 convex sets, functions, optimization problems
- 2 examples and applications
- 3 algorithms

Nonlinear optimization

traditional techniques for general nonconvex problems involve compromises

local optimization methods (nonlinear programming)

- find a point that minimizes f_0 among feasible points near it
- fast, can handle large problems
- require initial guess
- provide no information about distance to (global) optimum

global optimization methods

- find the (global) solution
- worst-case complexity grows exponentially with problem size

these algorithms are often based on solving convex subproblems

Brief history of convex optimization

theory (convex analysis): ca1900-1970

algorithms

- 1947: simplex algorithm for linear programming (Dantzig)
- 1960s: early interior-point methods (Fiacco & McCormick, Dikin, ...)
- 1970s: ellipsoid method and other subgradient methods
- 1980s: polynomial-time interior-point methods for linear programming (Karmarkar 1984)
- late 1980s-now: polynomial-time interior-point methods for nonlinear convex optimization (Nesterov & Nemirovski 1994)

applications

- before 1990: mostly in operations research; few in engineering
- since 1990: many new applications in engineering (control, signal processing, communications, circuit design, ...); new problem classes (semidefinite and second-order cone programming, robust optimization)